

POSTMARK AUTOMATIC LETTER OPENER

MODEL 3070
Features:



Model 3070

SPECIFICATIONS:

| | |
|-------------------------------|---|
| Length: | 44 inches / 1120 mm. Depth: 30 inches / 780 mm. Height: 45 inches/1160 mm. |
| Speed: | Theoretical speed (RPM): 40,000 envelopes per hour. |
| Production speed: | 20,000 per hours based upon a normal human being working 8 hours a day. Should you have a trained Octopus as an operator, please revert to above RPM! |
| Envelope Size: | All sizes and types. |
| Maximum Thickness: | 1/3" - 8 mm. |
| Depth of cut: | From 0 (no cut) to 0.125 inch/ 3mm. |
| Feeder capacity: | Approx. 200 envelopes. |
| Reverse flow conveyor: | Approx. 500. |
| Stand and waste bin: | Included. |
| Weight: | 227 lbs/103 kg. |
| Power: | 115V/60 Hz or 220V/50 Hz (3 motors x 60 watts). |

- **Milling Cutter Technology.** Protects the contents from being cut or damaged. Removes from 0 to 3mm (1/18") of the envelope edge. The removed material is in the form of tiny chips, which are deposited in the waste bin. Creates a soft, feathered edge opening, which prevents paper cuts and gives easy access to the contents.
- **High Speed.** Opens up to 40,000 envelopes per hour. Opens mixed mail - from the smallest to the largest - completely. Opens up to 1/3" (8 mm) thick envelopes. Entire system built to handle large flats and envelopes.
- **Reverse Flow Conveyor.** Allows operator to stand in one place to both feed and to remove opened envelopes. This increases the production rate by approx. 50 %.
- **Heavy Duty.** Solid metal construction throughout. Made of steel using the highest quality components. Has 2 motors for better performance and longer life.
- **Simple and reliable.** High degree of operational reliability.
- **Easy to Operate.**
- **Options/Accessories.** Counter and inkjet printer with dater, timer, numbering and bitmaps, and addressing capabilities (with complete software).



www.binatek.com